

형식 Model		처리 공기량 Air Processing Capacity L/min	사용압력 Working pressure Under:kPa	흡입온도 Linlet air temp Under:°C	주위온도 Ambient air temp Under:°C	포집효율 Collection efficiency μm	배관접속구경 Suction. exhaust port diameter	압력손실측정 접속구경 Port for pressure measuring Under:kPa	초기압력손실 Initial pressure drop Under:kPa	질량(kg) Mass kg
흡기 필터 Suction filter to collect oil mist out of inhaled air	RA-53S	210	-	40	40	-	RC3/4	Rc1/4	5.5	1.5
	RA-54S	440	-	40	40	-	RC3/4	Rc1/4	5.5	2.5
	RA-55S	770	-	40	40	-	RC3/4	Rc1/4	5.5	3.5
	RA-56S	1670	-	40	40	-	RC1	Rc1/4	5.5	6.5
	RA-57S	1670	-	40	40	-	RC1 1/4	Rc1/4	5.5	6.5
배기필터 Exhaust filter to collect dust out of exhaust air	RA-53D	210	70	80	40	0.3이상의 입자 99%	RC3/4	Rc1/4	5	2.0
	RA-54D	440	70	80	40	0.3이상의 입자 99%	RC3/4	Rc1/4	5	3.0
	RA-55D	770	70	80	40	0.3이상의 입자 99%	RC3/4	Rc1/4	5	4.5
	RA-56D	1670	70	80	40	0.3이상의 입자 99%	RC1	Rc1/4	5	9.0
	RA-57D	1670	70	80	40	0.3이상의 입자 99%	RC1 1/4	Rc1/4	5	9.0

구성

형식 Model		적용 펌프 Applicable pump	용도 Use	필터성분 Filter element
흡기 필터 Suction filter to collect oil mist out of inhaled air	RA-53S	KRX 1 · 3	펌프에 흡입되는 오일 미스트를 제거 Project pumps from entering oil mist	EM-250S
	RA-54S	KRX5		EM-500S
	RA-55S	KRX6		EM-750S
	RA-56S	KRX8		EM-1500S
	RA-57S	KRX10		EM-1500S
배기필터	SRA-53D	KRX 1 · 3		EM-250Z

Exhaust filter to collect dust out of exhaust air		
	RA-54D	KRX5
	RA-55D	KRX6
	RA-56D	KRX8
	RA-57D	KRX10

펌프에 배기 공기 안의 먼지 제거
Remove dust in the exhaust air.
(particle 0.3 μm 99%)

EM-500Z
EM-750Z
EM-1500Z
EM-1500Z